

Auto Capture



Motion is detected through PeepHole with the ambient light sensor

Fast Playback



Review your daily guests with the push of a button

Photo Visitor Log




Auto image capture through the PeepHole





Built-in Ambient light Sensor

The Motion Activated PeepHole Camera uses the traditional PeepHole thus not alerting anyone outside the door they are being photographed. Battery saving technology allows the PHVMAC to last for approximately **9000** triggers.





EP 2239946







Features



Easy to Install

Simple DIY three step install.





Photo Visitor Log

Auto image capture through the peephole.



Built-in Ambient light Sensor

Motion is detected through the peephole with the ambient light sensor.



Fast Image Playback

Review your daily guests with the push of a button.

Package contents



Motion Activated PeepHole Camera PHV MAC12 / PHV MAC14

Wirefree Security Surveillance










Enhanced Motion LED

Doorbell Sensor

Optional Accessories



Enhanced Knocking Sensor



Enhanced Motion Sensor

PHV MAC12 / PHV MAC14 Specifications

PeepHole barrel 12 mm

Fits any door 35~57 mm (1.38"~2.24") thick View Angle Regular: 92°, Zoom mode: 40°

PHV MAC14

PeepHole barrel 14 mm

35~57 mm (1.38"~2.24") thick Fits any door Regular: 92°, Zoom mode: 40° View Angle

A FOR BEST RESULTS PLEASE USE THE PEEPHOLE INCLUDED

3.0" TFT

Power Source

4 AA batteries (approx. 9,000 triggers)

File Format

JPEG, AVI

PeepHole, Base Flange, Tightening Tool, 4 AA Batteries, User Manual Micro SD card (If included with purchase)

Dimension

87x158x34mm (3.39" x 6.16" x 1.32") Size (DxWxH)

Weight 170 g (0.36 lb)



7F, No.75, Zhou Zi St., Taipei City 11493, Taiwan www.brinno.com

Phone:+886-2-8751-0306 Email: sales@brinno.com